





VOLTAGE RANGE: 50 - 1000V
CURRENT: 1.0 A

Features

- Glass Passivated Die Construction
- Ideally Suited for Automatic Assembly
- Low Forward Voltage Drop
- Low Power Loss
- Built-in Strain Relief
- Plastic Case Material has UL Flammability Classification Rating 94V-O

Mechanical Data

- Case: SMAF, Molded Plastic
- Terminals: Solder Plated, Solderable per MIL-STD-750, Method 2026
- Polarity: Color band denotes cathode end
- Mounting Position: Any
- Weight: 0.0018 ounce, 0.064 grams



| SMAF | | | |
|----------------------|-------|------|------|
| Dim | Min | Max | Typ |
| A | 4.75 | 4.85 | 4.80 |
| B | 3.68 | 3.72 | 3.70 |
| C | 2.57 | 2.63 | 2.60 |
| D | 0.097 | 1.03 | 1.00 |
| E | 1.38 | 1.42 | 1.40 |
| H | 0.13 | 0.17 | 0.15 |
| L | 0.63 | 0.67 | 0.65 |
| All Dimensions in mm | | | |

Maximum Ratings and Electrical Characteristics T_A = 25°C unless otherwise specified


Single phase, half wave, 60Hz, resistive or inductive load. For capacitive load, derate current by 20%.

| Characteristic | Symbol | GS1AF | GS1BF | GS1DF | GS1GF | GS1JF | GS1KF | GS1MF | Unit |
|---|-----------------------------------|-------------|-------|-------|-------|-------|-------|-------|------|
| Peak Repetitive Reverse Voltage | V _{RRM} | 50 | 100 | 200 | 400 | 600 | 800 | 1000 | V |
| Working Peak Reverse Voltage | V _{VRWM} | | | | | | | | |
| DC Blocking Voltage | V _R | | | | | | | | |
| RMS Reverse Voltage | V _{R(RMS)} | 35 | 70 | 140 | 280 | 420 | 560 | 700 | V |
| Average Rectified Output Current @ T _L = 100°C | I _O | 1.0 | | | | | | | A |
| Non-Repetitive Peak Forward Surge Current 8.3ms Single half sine-wave superimposed on rated load (JEDEC Method) | I _{FSM} | 30 | | | | | | | A |
| Forward Voltage @ I _F = 1.0A | V _{FM} | 1.10 | | | | | | | V |
| Peak Reverse Current @ T _A = 25°C At Rated DC Blocking Voltage @ T _A = 125°C | I _{RM} | 5.0 200 | | | | | | | μA |
| Reverse Recovery Time (Note 1) | t _{rr} | 2.5 | | | | | | | μS |
| Typical Junction Capacitance (Note 2) | C _j | 15 | | | | | | | pF |
| Typical Thermal Resistance (Note 3) | R _{θJL} | 30 | | | | | | | °C/W |
| Operating and Storage Temperature Range | T _j , T _{STG} | -65 to +175 | | | | | | | °C |


Note: 1. Measured with I_F = 0.5A, I_R = 1.0A, I_{rr} = 0.25A,
 2. Measured at 1.0 MHz and applied reverse voltage of 4.0 V DC.
 3. Mounted on P.C. Board with 8.0mm² land area.

RATINGS AND CHARACTERISTIC CURVES GS1AF THRU GS1MF


AVERAGE FORWARD RECTIFIED CURRENT, AMPERES




PEAK FORWARD SURGE CURRENT, AMPERES




INSTANTANEOUS FORWARD CURRENT, AMPERES



INSTANTANEOUS REVERSE CURRENT, MICROAMPERES



JUNCTION CAPACITANCE, pF



TRANSIENT THERMAL IMPEDANCE, °C/W

