

Features


- High switching speed: max. 4 ns
- Reverse voltage: max. 25V , 50V
- Peak reverse voltage: max. 35V, 75 V

Mechanical Data

- Case: DO-35, glass case
- Polarity: Color band denotes cathode
- Weight: 0.004 ounces, 0.13 grams



DO-35(GLASS)



Dimensions in millimeters

Maximum Ratings and Thermal Characteristics (Rating at 25 °C ambient temperature unless otherwise specified.)

Parameter	Symbol	Value	Unit
Maximum Peak Reverse Voltage	BAW75 BAW76	25 50	V
Maximum Reverse Voltage	BAW75 BAW76	35 75	V
Maximum Average Forward Current Half Wave Rectification with Resistive Load , f ≥ 50Hz	I _{F(AV)}	150 ⁽¹⁾	mA
Maximum Power Dissipation	P _D	500 ⁽¹⁾	mW
Maximum Surge Forward Current at t < 1μs , T _J = 25 °C	I _{FSM}	2	A
Maximum Junction Temperature	T _J	200	°C
Storage Temperature Range	T _S	-65 to + 200	°C

Note : (1) Valid provided that leads are kept at ambient temperature at a distance of 8mm from case.

Electrical Characteristics (T_J = 25°C unless otherwise noted)

Parameter	Symbol	Test Condition	Min	Typ	Max	Unit	
Reverse Current	BAW75 BAW76	I _R	V _R = 25 V V _R = 50 V	-	-	100 100	nA
Forward Voltage	BAW75 BAW76	V _F	I _F = 30 mA I _F = 100 mA	-	-	1.0 1.0	V
Reverse Breakdown Voltage	BAW75 BAW76	V _{(BR)R}	Test with 5μA pulses	35 75	-	-	V
Diode Capacitance	BAW75 BAW76	C _d	f = 1MHz ; V _R = 0	-	-	4.0 2.0	pF
Reverse Recovery Time	T _{rr}	I _F = 10 mA , I _R = 10 mA I _{rr} = 1mA	-	-	4	ns	



RATING AND CHARACTERISTIC CURVES (BAW75 ~ BAW76)

FIG. 1 ADMISSIBLE POWER DISSIPATION
VERSUS AMBIENT TEMPERATURE




FIG. 2 TYPICAL FORWARD VOLTAGE




FIG. 3 TYPICAL DIODE CAPACITANCE AS
A FUNCTION OF REVERSE VOLTAGE




FIG. 4 TYPICAL REVERSE CURRENT
VERSUS JUNCTION TEMPERATURE

